Procédés Hallier Collection

○ LED spotlight 9W

Spotlight ARCHE LED

A tool at the service of professionals





Procédés Hallier Collection

• LED spotlight 9W

Spotlight

ARCHE LED



Technical data



















Power: 9W

 $\textbf{CRI\,90}$ in 3000 K and in 4000 K

Integrated LED driver

Voltage In:

220 to 240 V, AC 50-60 Hz

output current 500 mA

Dimmable from 0% to 100% by manual potentiometer


Beam angle 20° or 40° to select (possibility to swap yourself)

Material: Steel

Finish: Powder painted Black, White or Grey - other colors on request

Dimensions (mm)





Options

BLUETOOTH controlled by iPhone, computer or dimmable bluetooth power switch ENOCEAN Rotary barn doors



Installation

Single circuit track adaptor

3-circuit track adaptor

Backplate

Other options available on request (clamp, ...)

Photometry

ARCHE LED 3000 K 9 W 500 mA CRI 90

20°	
	lux
1m (ø42cm)	/2257\
2m (ø84cm)	564
3m (ø125cm)	251
4m (ø167cm)	142

lux
/1574
394
175
98

Measures taken from right in the front of the spotlight

ARCHE LED 4000 K 9 W 500 mA CRI 90

ALIGHE EED TOOOK 3 VV 300 HI						
20°						
			Λ	lux		
	1m (ø42cm)		2505			
	2m (ø84cm)		626			
	3m (ø125cm)		278			
	4m (ø167cm)		156			

40°	
	lux
1m (ø69cm)	1660
2m (ø138cm)	415
3m (ø207cm)	185
4m (ø276cm)	103

Measures taken from right in the front of the spotlight



