Procédés Hallier Collection

Mini LED spotlight 3W

Spotlight LUNEO

A tool at the service of professionals





Procédés Hallier Collection

• Mini LED spotlight 3W



LUNEO



▼ Technical data

















Power: 3W

CRI 90 in 2800 K, 3000 K and CRI 95 in 4000 K (R9>90)

External LED driver (not included)

Voltage In:

220 to 240 V, AC 50-60 Hz

output current 700 mA

Beam angle 10° or 25° or 40° to select (possibility to swap yourself)

Material: Aluminium Finish: Black or Grey anodizing LED luminous flux*: 220 lm

Options

 $\textbf{BLUET00TH} \ controlled \ by \ iPhone, \ computer \ or \ dimmable \ bluetooth \ power \ switch \ ENOCEAN$

Rotary barn doors

Filter holder

Honeycomb filter

Electric connector

LED driver in 700 mA

LED driver 12V

Dimmable

Other colors available on request

Installation

Single circuit track adaptor 12 V


Rod

Backplate

Fastening bar

Other option available on request

Dimensions (mm)



Photometry

LUNEO 4000 K 3 W 700 mA CRI 95 10°

	lux
1m (ø70cm)	3940
1,5m (ø100cm)	1967
2m (ø130cm)	1110
3m (ø150cm)	432

Measures taken from right in the front of the spotlight

LUNEO 4000 K 3 W 700 mA

011133 40	
	lux
1m (ø140cm)	/1540
1,5m (ø200cm)	813
2m (ø250cm)	450
3m (ø350cm)	198

Measures taken from right in the front of the spotlight

LUNEO 4000 K 3 W 700 mA CRI 95 25°

	lux
1m (ø80cm)	/2230\
1,5m (ø120cm)	1090
2m (ø170cm)	620
3m (ø300cm)	275

Measures taken from right in the front of the spotlight





^{*} LED measurement source